

# AerFilm sofTouch®

## Technical Data Sheet

July 2020 • Page 1 of 1

PHYSICAL PROPERTIES			
PROPERTY	TEST METHOD	RESULT	
Weight	ISO 3801 method 5	< 300 g/m <sup>2</sup>	
Thickness <sup>1</sup>	-	<230 µm	
Abrasion Resistance <sup>1</sup>	ISO 9352 (CS10, 3.75N, 400 rev at 70 rev/min)	No penetration of cap layer	
UV Stability	ISO 105 – B02 (140 hrs, QUVA-340 Bulbs)	ΔE < 1.0	
Tear Strength	ISO 4674-1	Machine	Transverse
		>1 N	>1 N
Tensile Strength <sup>2</sup>	ISO 527-3/2/50	Machine	Transverse
		> 70 N	> 70 N

FLAMMABILITY PROPERTIES		
PROPERTY	TEST METHOD	RESULT
OSU Heat Release	FAR 25.853 (d), Amdt 25-116, Appendix F, Part IV	Meets requirement
NBS Optical Smoke Density	FAR 25.853 (d), Amdt 25-116, Appendix F, Part V	Meets requirement
Vertical Burn, 60 Sec	FAR 25.853 (a), Amdt 25-116, Appendix F, Part I (a)(1)(i)	Meets requirement

<sup>1</sup> Thickness and abrasion resistance may be affected by texture

<sup>2</sup> Tested on 15mm wide samples