

General Information

July 2020 • Page 1 of 1

AerFusion[®] fit is a state-of-the-art removable and repositionable flooring solution combining the well-known benefits of Schneller NTF with the ease of installation of a “ready to use” product and the following unique benefits;

- ❖ *Repositionable adhesive system provides the versatility required to meet precision installation requirements*
- ❖ *Adhesive system optimized for clean removal from floor substrate provides unparalleled efficiency during aircraft maintenance*
- Minimizes telegraphing (“read-through”) effect
- Better buckling resistance and dimensional stability than similar competitive products
- Unlimited color and design options
- Can be cut to size and/or pre-seamed to order
- Cost effective
- Easily removable liner to facilitate installation

Product Specifications

- *Complies with CFR/CS 25.853 (A), 12s Vertical Burn; Dimensionally stable per EN 434*
- Roll sizes up to 58” wide (1500cm), Typical roll length: 25 yards (7.7 meters)
- Nominal weight: < 2700 g/m² (80 oz./yd²)

Repositionable Adhesive System Specifications

- Integral, self-contained halogen free flame retardant double coated adhesive backing
- Adhesive system weight: 137 g/m² (4 oz./yd²)
- Repositionable pressure sensitive adhesive only weight: 30 g/m² (0.9 oz./yd²)
- Pressure sensitive adhesive shelf life: **7 months from Schneller manufacturing date** when stored under appropriate controlled conditions

Possible Applications

- Lavatory
- Galleys
- Entranceways
- Aisle ways

