

Indura GTglas®

General Information

July 2020 • Page 1 of 2

The fiberglass-reinforced laminates designed specifically for high wear, high traffic areas – with appropriate stiffness to conceal panel surface variations, and high impact resistance to protect underlying composite substrates. GTglas incorporates DuPont Tedlar® surface protection for low maintenance panels, resistant to graffiti, stains and solvents. Indura GTglas® is available in continuous roll form for high yield, low cost results. Also available in sheets upon request.

Product Features

- Applied on two dimensional panels, flat or with a single curvature.
- Integrally pigmented fiberglass base helps to hide dents, scratches and other wear-and-tear damage.
- Laminate bridges over and masks substrate panel imperfections.
- Stain, solvent and graffiti-resistant resulting in low maintenance and long life.
- Matte or glossy surface finish.
- Available in continuous rolls for optimum yield, lower shipping and storage costs. Also available in sheets (press textures) upon request.
- Unlimited color and design availability, including digital printing, flat, pearlescent and metallic colors.
- Factory-applied adhesives on request: Easier to install and environmentally friendly. Custom formulated, they adhere to stainless, aluminum, phenolic, gel coat, FRP, high-pressure laminates, and Tedlar®.
- Flexibility of material allows wrapping around radii as small as 0.125 in. (3.2mm).
- Approved and used by major intercity and commuter Rail Authorities worldwide.

Recommended Applications

- | | |
|---------------------------------|-----------------|
| • Entryways | • Doors |
| • Galley walls | • Luggage racks |
| • Partitions and bulkheads | • Lockers |
| • Inside/outside lavatory walls | • Wainscots |
| • Ceilings | |

Indura GTglas®

General Information

September 2010 • Page 2 of 2

Product Specifications

- Nominal Thickness MILs (mm): 15 (0.4)
- Nominal Weight (Oz/Yd²): 16
- Nominal Weight (g/m²): 510
- Available Textures: 620, 670, 855
- Available in continuous rolls up to 60 in. wide (152cm) for roll textures.
- Available with factory applied pressure sensitive (PSGT) adhesive.
- Available in custom cut-to-size sheets and strips.
- Available in custom cut-to-size sheets from rolls (R), 60 x 120 in. (152 x 305cm) sheets for press textures.
- Thoroughly tested to the most stringent flammability, smoke and toxicity requirements.